CITY SELECT SECOND SEAT KIT

Assembly Instructions



www.babyjogger.com



This Kit Includes:

1 City Select Seat 2 Adaptor Brackets



Adaptor Brackets




Always remove child from seat before removing seat from frame.



1 Turn seat over and insert foot bar into bracket.



3 Remove front mounting bracket plugs by firmly pressing the black button located above the front wheel and pulling up on the plug.




5 Align mounting brackets on the second seat with the top of the Adaptor Brackets.






2 Press gray button on foot bar and slide the foot bar into the bracket until it clicks into place.



NOTE: The Adaptor Brackets are labeled with an L or R for your convenience.

4 Insert right Adaptor Bracket into the right mounting bracket until it clicks into place. Repeat on left side.




6 Insert seat onto Adaptor Brackets until it clicks into place.

To Remove the City Select **Second Seat:**



1 Remove child from seat. Press grey buttons on seat mounting brackets and pull up until the seat detaches.



when second seat is not in use.

NOTE: Replace mounting bracket plugs

2 Press silver button on right Adaptor Bracket and pull upwards. Repeat on left side.


When Rear Facing:

NOTE: Your City Select Second Seat Kit can also be used facing the rear of the stroller.

8575 Magellan Parkway, Suite 1000 Richmond, VA 23227 T: 800-241-1848 • F: 804-262-6277 www.babyjogger.com



To make room for the seat's footwell: Unzip the right front and left front portions of the basket.



To adjust the footwell: Press both buttons on the side of the footwell and pull footwell upwards.